

📦 INSTALLATION INTERIOR



DESCRIPTION

Film adhésif miroir sans tain pour vitrage extérieur, le MIR 500X permet de voir sa

DURABILITY
Up to 15 years indoors.

MAINTENANCE
30 days after installation.

STORAGE
5 years away from moisture.

APPLICATION METHOD

The surface to be bonded must be free of dust, grease, or any other contaminant. Some materials like polycarbonate can cause bubbling. A compatibility test is therefore recommended.

GLAZING COMPATIBILITY



SINGLE



TEMPERED



DOUBLE <1.20M



DOUBLE >1.20M



LAMINATED

⚠ GLAZING COMPLIANCE

Glazing exposed to the sun must be of good quality and installed in compliance with glazing standards to guarantee the performance and durability of the film.

⚠ IMPORTANT NOTE

To ensure perfect uniformity across a project, it is recommended to exclusively use films from the same production batch and not mix different widths. Slight variations in tint or appearance may occur from one batch to another or depending on the widths, which could lead to visible differences once the strips are installed side by side.

🛡 PERFORMANCES

EN 410

SUPPORT	PET
↳ SUPPORT THICKNESS	60 microns
PROTECTOR	Silicone PET
↳ THICKNESS PROTECTOR	23 microns
ADHESIVE	Polymer Acrylic
COLOR	Silver mirror
APPLICATION FACE	exterior
VLT	15%
APPLICATION TEMPERATURE	min + 5°C

WARRANTY

5 years

📏 AVAILABLE DIMENSIONS

WIDTH

152 cm

LENGTHS (ROLLS)

10 m

30 m